MATERIAL SAFETY DATA SHEET
This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION							
NFPA Rating: Health-2; Flammability-1; Reactivity-0; Special HMIS Rating: Health-2; Flammability-1; Reactivity-0; Personal Protection-B							
Manufactured For: Hillyard Industries, Inc.	DOT Hazard Classification: ORM-D						
Address: 302 N. 4 <sup>th</sup> Street	Identity (trade name as used on label):						
Address: St. Joseph, MO 64501	LEMON FURNITURE POLISH						
DI (040)000 4004 4 0005 HII (/ HIII I	Part# HIL0105254						
	umber:         A00135         Revision- 14						
Emergency Response Number: Chemtrec 1-800-424-9300 Date Prepared: 04/12/06 Prepared By: AH/IB  NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071							
SECTION 1 - MATERIAL I			MATION				
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	DENTIFIC	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		O/ to Hambon	III LIST	(ppm)	TLV (ppm)	Ref. Source **	
HYDROTREATED LIGHT PETROLEUM DISTILLATES		64742-47-8	No	5 mg/m3	5 mg/m3	d	
				(mist)	(mist)		
PETROLEUM DISTILLATES	8052-41-3	No	100	100	d		
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point:     N/A     Specific Gravity (H2O=1):     Concentrate Only = 0.938       Vapor Pressure:     PSIG @ 70°F (Aerosols):     Max.50     Vapor Pressure (Non-Aerosols)(mm Hg and Temperature):     N/A							
Vapor Density (Air = 1): N/E	poration Rate ( = 1): N/E						
Solubility in Water: Partial Water Reactive: No							
Appearance and Odor: Cream color, lemon fragrance.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME PROJECTION TEST	Auto Igr	nition Temperature		nability Limits			
(aerosols): extinguishes flame:		N/E	% LEL	: N/E	% UEL:	N/E	
NOT CATEGORIZED AS FLAMMABLE.  FLASH POINT AND METHOD USED (non-aerosols): N/A	EVT	INCHIEUED MEDIA: E	ioom dru	shamical aarl	on diovido w	otor fog	
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water fog. SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizers.  Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA  REIMARY POLITES OF ENTRY: 1 Y I NILIAL ATION: 1 I NICESTION: 1 Y I SVIN ADSORPTION: 1 I EVE. 1 I NICE HAZARDOLIS							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
<b>Inhalation:</b> Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Slight irritation.  Skin Contact: Slight irritation.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Petroleum distillate has caused kidney injury in							
laboratory animals. Stomach and intestine irritant.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Latex, if skin easily irritated.  Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.  Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH LIQUID TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF Cources.	CHILDREN.	Avoid food contamina	tion. Avoid	d breathing va	pors. Remove	ignition	
144. 6. 6				***			

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only