

VISTA PAINT CORP -- 4000 UNIPRIME -- 8010-00N021431

===== Product Identification =====

Product ID:4000 UNIPRIME
MSDS Date:06/16/1988
FSC:8010
NIIN:00N021431
=== Responsible Party ===
Company Name:VISTA PAINT CORP
Address:2020 E ORANGETHORPE AVE
City:FULLERTON
State:CA
ZIP:92631
Country:US
Info Phone Num:714-680-3800
Emergency Phone Num:714-680-3800
CAGE:0C4T4

===== Contractor Identification =====

Company Name:VISTA PAINT CORP
Address:2020 E ORANGETHORPE AVE
Box:City:FULLERTON
State:CA
ZIP:92631
Country:US
Phone:714-680-3800
CAGE:0C4T4

===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:AMMONIA (SARA III)
CAS:7664-41-7
RTECS #:BO0875000
OSHA PEL:50 PPM
ACGIH TLV:25 PPM/35 STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:PROPIONIC ACID, 2-METHYL-, MONOESTER WITH
2,2,4-TRIMETHYL-1, 3-PENTANEDIOL; (TEXANOL)
CAS:25265-77-4
RTECS #:UF6000000

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION OF HIGH VAPOR
CONCENTRATIONS MAY HAVE RESULTS RANGING FROM DIZZINESS AND
HEADACHES TO UNCONSCIOUSNESS.

Explanation of Carcinogenicity:NOT RELEVANT.
 Effects of Overexposure:SEE HEALTH HAZARDS.
 Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INGEST:DRINK WATER TO DILUTE. DO NOT INDUCE VOMIT.
 INHAL:REMOVE TO FRESH AIR. SKIN:WASH W/SOAP & WATER. EYES:FLUSH W/
 WATER FOR AT LEAST 15 MINUTES OR UNTIL IRRITATION SUBSIDES.

===== Fire Fighting Measures =====

Flash Point:248F,120C
 Lower Limits:0.62%
 Upper Limits:4.24%
 Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL.
 Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL
 PROTECTIVE EQUIPMENT .
 Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT. CONTAINERS MAY
 EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN SPILLS IMMEDIATELY WITH ABSORBANT SUCH
 AS CLAY OR SAND.
 Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT OR FLAME.
 Other Precautions:AVOID UNNECESSARY EXPOSURE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID EXCESSIVE VAPOR INHALATION. USE NIOSH/MSHA
 APPROVED RESPIRATOR IF TLV IS EXCEEDED.
 Ventilation:MECHANICAL VENTILATION MAY BE USED IF NEEDED TO CONTROL
 MIST OR VAPOR.
 Protective Gloves:NEOPRENE GLOVES.
 Eye Protection:CHEM WORK GOGG/FULL LENGTH FCSHLD.
 Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
 Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
 Supplemental Safety and Health
 NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1
 Boiling Pt:B.P. Text:250F,121C
 Vapor Pres:0.02 MM HG
 Spec Gravity:1.334
 Solubility in Water:YES
 Appearance and Odor:LIQUID, MILD ODOR.
 Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
 STRONG OXIDIZERS.
 Stability Condition to Avoid:CONTACT WITH STRONG OXIDIZERS.