



Gum Remover

Version Number: 1

Preparation date: 2014-05-19

1. IDENTIFICATION

Product name: Gum Remover
Product Code: 95628817
SDS #: MS0800327
Recommended use: • Carpet Care
Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier: US Headquarters Sealed Air 8215 Forest Point Blvd. Charlotte, NC 28273-5509 Phone: 1-888-352-2249 SDS Internet Address: https://sds.sealedair.com	Canadian Headquarters Sealed Air - Canada 3755 Laird Road Mississauga, Ontario L5L 0B3 Phone: 1-800-668-7171
--	--

Emergency telephone number: 1-888-660-6737

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Flammability	Extremely flammable aerosol, Category 1



Signal Word:

Danger.

Precautionary Statements

Avoid contact with eyes, skin and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not incinerate. Wash affected areas thoroughly after handling. Wear chemical-resistant gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Dispose of in accordance with all federal, state and local applicable regulations.

Health hazards not otherwise classified (HHNOC) - Not applicable

Physical hazards not otherwise classified (PHNOC) - Not applicable

Classification for the diluted product @ RTU

This product is intended to be used neat.

Precautionary Statements

None required.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Classified Ingredients**

Ingredient(s)	CAS #	Weight %
Butane	106-97-8	60 - 70%
Propane	74-98-6	30 - 40%
Ethyl alcohol	64-17-5	10 - 20%

*Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES**Undiluted Product:**

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

Skin: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation: No specific first aid measures are required.

Ingestion: Rinse mouth with water.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed: Not applicable.

Aggravated Medical Conditions: None known.

Diluted Product:

This product is intended to be used neat.

Eyes: See undiluted product information above.

Skin: See undiluted product information above.

Inhalation: See undiluted product information above.

Ingestion: See undiluted product information above.

5. FIRE-FIGHTING MEASURES

Specific methods:

Aerosol Product - Containers may rocket or explode in heat of fire

Suitable extinguishing media:

Dry chemical, water spray, foam, carbon dioxide.

Specific hazards:

Aerosol product - Containers may rocket or explode in heat of fire. Keep product and empty container away from heat and sources of ignition. NFPA 30B Level 3 Aerosol.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions

Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

and clean-up methods:

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Do not taste or swallow. Wash thoroughly after handling. CONTENTS UNDER PRESSURE. Do not puncture or incinerate. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 degrees C or 120 degrees F. Exposure to heat may cause bursting. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.

Aerosol Level (if applicable) : Level 3

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS #	ACGIH	OSHA
Butane	106-97-8	1000 ppm (STEL)	-
Propane	74-98-6	-	1000 ppm (TWA) 1800 mg/m ³ (TWA)
Ethyl alcohol	64-17-5	1000 ppm (STEL)	1000 ppm (TWA) 1900 mg/m ³ (TWA)

Undiluted Product:

Engineering measures to reduce exposure:

No special ventilation requirements General room ventilation is adequate

Personal Protective Equipment

Eye protection:	No personal protective equipment required under normal use conditions.
Hand protection:	Chemical-resistant gloves.
Skin and body protection:	No special requirements under normal use conditions.
Respiratory protection:	No special requirements under normal use conditions.
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

This product is intended to be used neat.

Personal Protective Equipment

Eye protection:	No personal protective equipment required under normal use conditions.
Hand protection:	Chemical-resistant gloves.
Skin and body protection:	No personal protective equipment required under normal use conditions.
Respiratory protection:	No personal protective equipment required under normal use conditions.
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol

Evaporation Rate: No information available

Odor threshold: No information available.

Melting point/range: Not determined

Autoignition temperature: No information available

Solubility in other solvents: No information available

Density: 4.75 lbs/gal 0.57 Kg/L

Bulk density: No information available

Flash point: 55 °F 12.8 °C

Dilution Flash Point: 55 °F 12.8 °C

Elemental Phosphorus: 0 % by wt.

pH: Not applicable

Dilution pH: No information available. @ RTU

Metal Corrosion: Not determined

Explosion limits: - upper: Not determined - lower: Not determined

Color: Clear, Colorless

Odor: Cherry

Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Partially Soluble

Relative Density (relative to water): 0.5700

Vapor density: No information available

Vapor pressure: No information available.

Partition coefficient (n-octanol/water): No information available

Viscosity: No information available

VOC: 100 % *

VOC % by wt. at use dilution 100 % *

Flammability (Solid or Gas): Not applicable

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity:

Not Applicable

Stability:

The product is stable

Hazardous decomposition products:

None reasonably foreseeable.

Materials to avoid:

Do not mix with any other product or chemical unless specified in the use directions.

Conditions to avoid:

Keep away from open flames, hot surfaces and sources of ignition. Prolonged exposure to heat above 120 °F (49 °C).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Eye contact, Skin contact, Inhalation

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure**Skin contact:** Causes skin irritation. Symptoms may include pain (which may be delayed), redness, and/or discomfort.**Eye contact:** Causes eye irritation. Symptoms may include discomfort, redness, and watering.**Ingestion:** May be irritating to mouth, throat and stomach. Symptoms may include stomach pain and nausea.**Inhalation:** May be irritating to nose, throat, and respiratory tract. Symptoms may include coughing and difficulty breathing.**Sensitization:** No known effects.**Target Organs (SE):** None known**Target Organs (RE):** None known**Carcinogen Listings: Statement per route of exposure or specific component** Ethyl alcohol is only classified as an IARC 1 carcinogen when it is meant for ingestion in alcoholic beverages. We do not produce alcoholic beverages; therefore it is not considered a carcinogen in our products.

Ingredient(s)	CAS #	NTP	IARC	OSHA
Ethyl alcohol	64-17-5		-	

Numerical measures of toxicity**12. ECOLOGICAL INFORMATION****Ecotoxicity:** No information available.**Persistence and Degradability:** No information available.**Bioaccumulation:** No information available.**13. DISPOSAL CONSIDERATIONS****Waste from residues / unused products:** This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations.**Contaminated Packaging:** Do not re-use empty containers.**RCRA Hazard Class (undiluted product):** D001 Ignitable Waste**14. TRANSPORT INFORMATION****DOT/TDG/IMDG:** Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, <http://naextranet.diversey.com/dot/>, for up to date shipping information.**DOT (Ground) Bill of Lading Description:** LTD. QTY.**IMDG (Ocean) Bill of Lading Description:** UN1950, AEROSOLS, 2.1, LTD. QTY.**15. REGULATORY INFORMATION****International Inventories at CAS# Level**

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.**RIGHT TO KNOW (RTK)**

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Butane	106-97-8	X	X	X	-
Propane	74-98-6	X	X	X	-
Ethyl alcohol	64-17-5	X	X	X	-

CERCLA/ SARA

SARA 311/312 Hazard Categories

Immediate: X
Delayed: -
Fire: X
Reactivity: -
Sudden Release of Pressure: X

Canadian Regulations

Ingredient(s)	CAS #	NPRI
Propane	74-98-6	X
Ethyl alcohol	64-17-5	X

16. OTHER INFORMATION

NFPA (National Fire Protection Association)
Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 2
Flammability 4
Instability 0

Version Number: 1
Preparation date: 2014-05-19

Reason for revision: Not applicable
Prepared by: NAPRAC
Additional advice: • Contains an added fragrance, see "Odor" heading in section 9 for specific description

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.