

# SAFETY DATA SHEET

## 1. Identification

**Product number** CS227 (1000024181)  
**Product identifier** Pro Series Stainless Steel & Metal Polish  
**Company information**  
CSI Inc.  
1005 S. Westgate Drive  
Addison, IL 60101 United States  
**Company phone**  
**Emergency telephone US** 800-252-4731  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 01  
**Recommended use** Cleaner/Polish  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Not classified.  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger  
**Hazard statement** Extremely flammable aerosol.  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.  
**Response** Wash hands after handling.  
**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Hazard(s) not otherwise classified (HNOC)** Not classified.  
**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3  
Hazardous to the aquatic environment, long-term hazard Category 3

### Supplemental information

**Hazard statement** Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**Prevention** Avoid release to the environment.

49.8% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 49.78% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

### Mixtures

Hazardous components			
Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
Acetone		67-64-1	2.5 - 10
Propane		74-98-6	2.5 - 10
Other components below reportable levels			60 - 80

#: This substance has workplace exposure limit(s).  
vPvB: very persistent and very bioaccumulative substance.  
PBT: persistent, bioaccumulative and toxic substance.

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

<b>Inhalation</b>	If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Immediately flush skin with plenty of water. Get medical attention immediately. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention immediately.
<b>Ingestion</b>	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth thoroughly. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Keep victim warm. Keep victim under observation.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Powder. Water. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.
--	---

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. For waste disposal, see section 13 of the MSDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage**

**Precautions for safe handling**

Vapors may form explosive mixtures with air. May be ignited by open flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid exposure - obtain special instructions before use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Do not use in areas without adequate ventilation. Observe good industrial hygiene practices. Wash thoroughly after handling. Do not empty into drains.

**Conditions for safe storage, including any incompatibilities**

Avoid exposure - obtain special instructions before use. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol. Level 3 Aerosol.

**8. Exposure controls/personal protection**

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Avoid exposure - obtain special instructions before use. Wear tight-fitting goggles or face shield. Face-shield.

**Hand protection**

Avoid exposure - obtain special instructions before use. Wear protective gloves.

<b>Other</b>	Avoid exposure - obtain special instructions before use. Wear chemical protective equipment that is specifically recommended by the manufacturer.
<b>Respiratory protection</b>	Avoid exposure - obtain special instructions before use. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Do not get in eyes. Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Appearance</b>	Clear.
<b>Color</b>	Colorless.
<b>Form</b>	Aerosol.
<b>Physical state</b>	Gas.
<b>Boiling point</b>	447.8 °F (231 °C) estimated
<b>Flash point</b>	-156.00 °F (-104.44 °C) Propellant estimated
<b>Melting point/freezing point</b>	Not available.
<b>Odor</b>	mint-like
<b>pH</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Vapor pressure</b>	45 psig @70F estimated
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Specific gravity</b>	0.521 estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Risk of ignition.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Not available.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

#### Acute toxicity

Product	Species	Test Results
14 OZ PRO SERIES METAL POLISH LB 12PK (CAS Mixture)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	202.2245 ml/kg, estimated
	Rat	95849 mg/kg
<i>Inhalation</i>		
LC50	Mouse	3330.8088 mg/l, 2 Hours, estimated
	Rat	54545.4531 mg/l, 6 Hours, estimated

Product	Species	Test Results
		16138.5059 mg/l, 15 Minutes, estimated
		3306.5991 mg/l, 4 Hours, estimated
		506.5723 mg/l, 8 Hours, estimated
		255 mg/l/4h
<i>Oral</i>		
LD50	Mouse	30333.6699 mg/kg, estimated
	Rabbit	53993.9336 mg/kg, estimated
	Rat	58514.0313 mg/kg, estimated
<i>Other</i>		
LD50	Mouse	13082.2705 mg/kg, estimated
	Rat	55611.7305 mg/kg, estimated
Components	Species	Test Results
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	20000 mg/kg 20 ml/kg
<i>Inhalation</i>		
LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
<i>Other</i>		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes 658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Harmful in contact with eyes.
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Suspect cancer hazard.
<b>Reproductive toxicity</b>	Avoid exposure to women during early pregnancy.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not likely, due to the form of the product.

**Chronic effects** Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Prolonged or repeated exposure may cause lung injury. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.

**Further information** Symptoms may be delayed.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
14 OZ PRO SERIES METAL POLISH LB 12PK (CAS Mixture)		
Crustacea	EC50	Daphnia
Fish	LC50	Fish
		52151.668 mg/l, 48 hours, estimated
		17188 mg/L, 96 Hours
Components	Species	Test Results
Acetone (CAS 67-64-1)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		21.6 - 23.9 mg/l, 48 hours
		4740 - 6330 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

Acetone	-0.24
Propane	2.36
Butane	2.89

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**US RCRA Hazardous Waste U List: Reference**

Acetone (CAS 67-64-1) U002

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

**DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols
<b>Transport hazard class(es)</b>	2.1
<b>Subsidiary class(es)</b>	Not available.
<b>Packing group</b>	Not available.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Labels required</b>	2.1
<b>Special provisions</b>	153, N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1
<b>Subsidiary class(es)</b>	-
<b>Packaging group</b>	Not available.
<b>Environmental hazards</b>	No
<b>Labels required</b>	2.1
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Packaging Exceptions</b>	LTD QTY

#### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	2
<b>Subsidiary class(es)</b>	-
<b>Packaging group</b>	Not available.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No
<b>Labels required</b>	Not available.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

#### DOT



#### IATA; IMDG



## 15. Regulatory information

#### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

LISTED

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

### DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

**Food and Drug Administration (FDA)** Not regulated.

## US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) 500 lbs

Propane (CAS 74-98-6) 500 lbs

### US. Pennsylvania RTK - Hazardous Substances

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 06-18-2014

**Version #** 01



**Further information**

Not available.

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information**

Product and Company Identification: Product Review  
Composition / Information on Ingredients: Ingredients  
Physical & Chemical Properties: Multiple Properties  
Transport Information: Proper Shipping Name/Packing Group  
Regulatory Information: United States  
HazReg Data: North America