

W W HENRY CO -- 204 PLASTIC ROOF CEMENT -- 8030-00F004700

=====
Product Identification
=====

Product ID:204 PLASTIC ROOF CEMENT

MSDS Date:01/01/1994

FSC:8030

NIIN:00F004700

MSDS Number: BWTDF

=== Responsible Party ===

Company Name:W W HENRY CO

Address:2911 SLAUSON AVE

City:HUNTINGTON PARK

State:CA

ZIP:90255-5000

Country:US

Info Phone Num:213-583-5000

Emergency Phone Num:213-583-5000

CAGE:EO927

=== Contractor Identification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

Company Name:W W HENRY CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-5000

Country:US

Phone:213-583-4961

CAGE:EO927

=====
Composition/Information on Ingredients
=====

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPHTHANES
MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 20-25%

Other REC Limits:100 PPM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:ASBESTOS (BULK), AMPHIBOLE, ASBESTOS FIBER, SERPENTINE
(CONFIRMED HUMAN CARCINOGEN BY NTP/OSHA/ACGIH/IARC-GROUP1) *95-1*

CAS:1332-21-4

RTECS #:CI6475000

Fraction by Wt: 12-14%

Other REC Limits:A1 HUMAN CARCINOGEN

OSHA PEL:2 FB/CC

ACGIH TLV:2 FB/CC

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingrid Name:VOLATILE ORGANIC COMPOUNDS: 300 G/L
RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:MAY CAUSE IRRITATION OF NOSE, THROAT &
EYES. EXTREME EXPOSURE MAY CAUSE DEATH BY PARALYSIS OF RESPIRATORY
CENTER.
Explanation of Carcinogenicity:SEE INGREDIENTS
Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, GIDDINESS,
UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:PRE-EXISTING ANEMIA,
RESPIRATORY/LIVER AILMENT.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NEEDED. EYES:
WASH W/WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. OBTAIN
MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point:120F
Lower Limits:1
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. CLEAN UP AS SOON
AS POSSIBLE W/ABSORPTIVE MATERIAL/CLAY/DIATOMACEOUS EARTH/OTHER
NON-FLAMMABLE ABSORBENTS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT & OTHER IGNITION
SOURCES.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR ORGANIC RESPIRATOR/SUPPLIED AIR SYSTEM IF
TLV IS EXCEEDED.
Ventilation:SUFFICIENT TO KEEP VAPORS